

EAST - [10692404.wsp:1]

File View Edit Tools Window Help

Search List Browse Queue Clear

DBs US-PGPUB:USPA ☒ Plurals

Default operator: OR ☒ Highlight all hit terms initially

19 and (control near5 controller)

☒ L2: (1) 1 and controller
☒ L1: (4) tracking near8 "RF measurement"
☒ L3: (79) tracking and "RF measurement"
☒ L4: (0) 3 and "under the controller"
☒ L5: (0) 3 and "under control of the controller"
☒ L6: (21) 3 and (control near5 controller)
☒ L7: (9) 6 and "baseband signal"
☒ L8: (1) 7 and "test signal"
☒ L9: (1) 7 and (test\$3 adj signal)
☒ L10: (99) tracking and ("RF measurement" or "radio frequency measurement")
☒ L11: (28) 10 and (control near5 controller)
☒ L12: (9) 11 and "baseband signal"
☒ L13: (1) 12 and "test signal"
☒ L14: (6) 11 and "baseband signal"
☒ L15: (129615) "455"/\$.ccls. or "375"/\$.ccls.
☒ L16: (4284) 15 and (tracking and measurement)
☒ L17: (2763) 16 and (RF or "radio frequency")
☒ L18: (122) 17 and "test signal"
☒ L19: (11) 18 and "baseband signal"
☒ L20: (4) 19 and (control near5 controller)

Failed

BRS form IS&R form Image Text HTML

	U	I	Document ID	Issue Date	Pages	Title	Current OR	Current	Ret	Inventor
1	<input type="checkbox"/>	<input type="checkbox"/>	US 4860321 A	19890822	34	Lock detector for feedback loops	375/343	331/64; 375/333;		von der Embse; U. A.
2	<input type="checkbox"/>	<input type="checkbox"/>	US 4706263 A	19871110	34	Data communications receiver operable in highly stressed en	375/343	375/350; 375/376		von der Embse; U. A.
3	<input type="checkbox"/>	<input checked="" type="checkbox"/>	US 4689806 A	19870825	34	Receiver mode control for acquiring and tracking a signa	375/361	370/317; 375/375		von der Embse; U. A.
4	<input type="checkbox"/>	<input checked="" type="checkbox"/>	US 4627079 A	19861202	34	Method and apparatus for acquiring and tracking a com	375/343	324/76.21; 324/76.29;		von der Embse; Urban A.

Hits Details HTML

Ready

EAST - [10692404.wsp:1]

File View Edit Tools Window Help

Drafts

Pending

Active

- L2: (1) 1 and controller
- L1: (4) tracking near8 "RF measurement"
- L3: (79) tracking and "RF measurement"
- L4: (0) 3 and "under the controller"
- L5: (0) 3 and "under control of the controller"
- L6: (21) 3 and (control near5 controller)
- L7: (9) 6 and "baseband signal"
- L8: (1) 7 and "test signal"
- L9: (1) 7 and (test\$3 adj signal)
- L10: (99) tracking and ("RF measurement" or "radio frequency measurement")
- L11: (28) 10 and (control near5 controller)
- L12: (9) 11 and "baseband signal"
- L13: (1) 12 and "test signal"
- L14: (6) 11 and "baseband signal"

Failed

Saved

Search List Browse Open Clear

DBs USPAT ☒ Bards

Default operator: OR ☒ Highlight all hit terms initially

11 and "baseband signal"

BRS form IS&R form Image Text HTML

	U	1	Document ID	Issue Date	Pages	Title	Current OR	Current	Ret	Inventor
2	<input type="checkbox"/>	<input type="checkbox"/>	US 6898233 B2	20050524	60	Programmable modem apparatus for transmitting and	375/130	375/146, 375/222		Philips; Lieven et al.
3	<input type="checkbox"/>	<input type="checkbox"/>	US 6597727 B2	20030722	62	Programmable modem apparatus for transmitting and	375/147	375/222, 375/316		Philips; Lieven et al.
4	<input type="checkbox"/>	<input type="checkbox"/>	US 6307877 B1	20011023	61	Programmable modem apparatus for transmitting and	375/130	375/222		Philips; Lieven et al.
5	<input type="checkbox"/>	<input checked="" type="checkbox"/>	US 6212566 B1	20010403	60	Interprocess communication protocol system modem	709/230	709/200, 709/231		Vanhooft, Jan et al.
6	<input type="checkbox"/>	<input type="checkbox"/>	US 5872810 A	19990216	61	Programmable modem apparatus for transmitting and	375/222	375/130		Philips; Lieven et al.

Hits Details HTML

Ready NUM